

# SIGHT MARK



## SPECIFICATIONS

Reticle type	65 MOA Circle Dot Crosshair (60 MOA circle w/5MOA sub-tension, 2 MOA central dot)
Illuminated Reticle color	Red
Brightness settings	off, 1-6, NV1-NV6
Magnification	1x
Window dimension	33x24mm
Window material	glass
Field of view (m@100m)	35
Field of view (ft@100yd)	105
Eye relief	unlimited
Windage / Elevation adjustment	120 MOA
MOA adjustment	1" (1 click)
Finish/color	Matte black
Body material	Magnesium alloy
Parallax setting	10yd
Maximum recoil	up to .50 cal
IP rating	IP68- submergible to 40ft
Lens coatings	AR Red
Mount type	weaver/picatinny
Battery type	CR2
Battery life	90-1000hrs
Battery voltage	3V
Operating temperature	-20 to 140°F
Dimensions	103x58x61mm
Weight	8oz

## SIGHTMARK® M-SPEC REFLEX SIGHT

### FEATURES

- ✦ Cast magnesium alloy housing with protective shield
- ✦ IP68 Waterproof rating - submergible up to 40ft
- ✦ Low power consumption
- ✦ Digital switch controls
- ✦ Variable reticle brightness with night vision modes
- ✦ Interlok™ internal locking system
- ✦ Lightweight
- ✦ Shockproof
- ✦ Wide field of view
- ✦ Parallax corrected

### INCLUDED

- ✦ Neoprene cover
- ✦ Adjustment tools
- ✦ Battery

Featuring a digital switch control with six variable brightness levels for daytime use and six settings in night vision mode, the new Sightmark® Ultra Shot M-Spec Reflex Sight is built for adaptation to any environment a shooter finds himself in. Its magnesium alloy housing offers exceptional durability along with a battery life of up to 1,000 hours of superior functionality. The device features a protective hood that shields it from impact, a shock-proof frame for up to .50 caliber recoil and is fully submersible. Equipped with dual-pane glass and a parallax-corrected lens system, the Ultra Shot M-Spec allows shooters to sight accurately from 10 yards to infinity.